

1. ČELIČNA UŽAD I LANCI Wire ropes and chains


1.3. Nerotirajuće uže

Čelično uže: 19x7+čelična jezgra

Wire rope: 19x7+IWRC non-rotating, non-compacted

CE 2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1960 N/mm ²	Težina (kg/100m)
Diameter	MBL	Weight
4	10,30	6,4
5	16,10	10,0
6	23,10	14,4
7	31,5	19,7
8	41,1	25,7
9	52,1	32,50
10	64,3	40,10
11	77,8	48,50
12	92,6	57,70
13	108,7	67,8
14	126,0	79,0
15	145,0	90,0
16	165,0	103,0
18	208,0	130,0
19	232,0	145,0
20	257,0	160,0



- EN 12385-4
- DIN 3069
- završna obrada: el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1960 N/mm²




Čelično uže: 35Wx7+čelična jezgra

Wire rope: 35Wx7+IWRC rotation resistant, non-compacted

CE 2.1 2.2 3.1 BL

Promjer (mm)	Min. prekidna sila (kN) 1960 N/mm ²	Min. prekidna sila (kN) 2160 N/mm ²	Težina (kg/100m)
Diameter	MBL	MBL	Weight
8	45,20	48,4	29,10
9	57,20	61,2	36,80
10	70,60	75,60	45,40
11	85,40	91,50	54,9
12	102,0	109,0	65,4
13	119,0	128,0	76,7
14	138,0	148,0	89,0
16	181,0	194,0	116,0
18	229,0	245,0	147,0
20	282,0	302,0	182,0
22	342,0	366,0	220,0
24	406,0	435,0	262,0
26	477,0	511,0	307,0
28	553,0	593,0	356,0
32	723,0	774,0	465,0
36	914,0	980,0	588,0
38	1020,0	1090,0	656,0
40	1130,0	1210,0	726,0



- EN 12385-4
- DIN 3072
- završna obrada: el. galvanizirano ili vruće cinčano
- čvrstoća žice: 1960 N/mm² ili 2160 N/mm²

